

Cindol® 3106

Heavy duty, light viscosity straight oil

DESCRIPTION

Cindol 3106 was developed specifically for general machining and grinding of hard-to-machine metals such as: high nickel alloys; alloy steels; stainless steels and cobalt chrome. Its light viscosity makes it ideal for use with through coolant fed tooling.

Cindol 3106 contains a unique lubrication additive, ND. It dramatically lowers the coefficient of friction of steel to aluminum and aluminum to aluminum and is also used on stainless steel, bronze, brass, galvanized steel, titanium and other metals.

FEATURES / BENEFITS

- Increased tool life
- Improved surface finish
- Excellent lubricity
- Reduced chip welding
- Versatility for all tough operations

DATA (TYPICAL VALUES)

Appearance	Light amber liquid
Viscosity @ 40°C, cSt	18
Flash Point, °C (C.O.C.)	179
Specific Gravity	0.92

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

DM 16.01 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.